

Docket Number  
36856.1433

**IN THE UNITED STATES PATENT AND TRADEMARK OFFICE**

Applicant(s): Kenjiro OKAGUCHI et al.  Serial No.: Currently unknown  Filing or 371(c) Date: Concurrently herewith  Title: OSCILLATOR CIRCUIT INCLUDING SURFACE ACOUSTIC WAVE SENSOR AND BIOSENSOR APPARATUS	International Application No.: PCT/JP2004/013072   International Filing Date: September 8, 2004
--	--

**PRELIMINARY AMENDMENT**

Mail Stop PCT  
Commissioner for Patents  
P.O. Box 1450  
Alexandria, VA 22313-1450

Sir:

Prior to examination on the merits of the above-identified patent application,  
Applicants respectfully request entry and consideration of the following Amendment:

- ☒ **Amendments to the Specification** begin on page 2 of this paper.
- ☒ **Amendments to the Drawings** begin on page 5 of this paper and include an attached replacement sheet.
- ☒ **Amendments to the Claims** are reflected in the listing of the claims which begins on page 6 of this paper.
- ☒ **Remarks/Arguments** begin on page 8 of this paper.

Please note, if a box is not checked, then no corresponding amendment is being made.

International Application No.: PCT/JP2004/013072

U.S. Patent Application No.: Unknown

April 7, 2006

Page 2 of 10

**AMENDMENTS TO THE SPECIFICATION:**

A substitute specification and a marked-up copy of the English translation of the originally filed PCT application are attached hereto.

Please replace the Title of the Invention originally filed with the above-identified patent application with the following new Title:

OSCILLATOR CIRCUIT INCLUDING SURFACE ACOUSTIC WAVE SENSOR  
AND BIOSENSOR APPARATUS

International Application No.: PCT/JP2004/013072  
U.S. Patent Application No.: Unknown  
April 7, 2006  
Page 3 of 10

**IN THE ABSTRACT:**

Please replace the Abstract of the Disclosure originally filed with the above-identified patent application with the following new Abstract of the Disclosure:

## ABSTRACT OF THE DISCLOSURE

A surface-acoustic-wave-sensor-included oscillator circuit does not cause separation of an electrode film due to application of a bias voltage and can reliably accurate operate even if liquid is adhered thereto. The surface-acoustic-wave-sensor-included oscillator circuit includes interdigital electrode disposed on a piezoelectric substrate and a reaction film that is arranged so as to cover the interdigital electrodes and bound to a target substance or a binding material to be bound to the target substance. A surface acoustic wave sensor that is capable of detecting a bit of mass loading on the basis of a variation in frequency is connected as a resonator in the surface-acoustic-wave-sensor-included oscillator circuit. Direct-current cutting capacitors are connected in series to the surface acoustic wave sensor, and the direct-current cutting capacitors respectively define impedance matching circuits in the surface-acoustic-wave-sensor-included oscillator circuit.

**AMENDMENTS TO THE DRAWINGS:**

The attached sheet of Drawings includes changes to Figs. 10, 11 and 12. This sheet, which includes Figs. 10, 11 and 12, replaces the original sheets including Figs. 10, 11 and 12.

Attachment: two (2) Replacement Sheets.